



Top Deck Systems, Inc. 44753 Centre Court, Clinton Twp. MI 48038

## **BARRICADE/TEMPORARY WALL SPECIFICATIONS**

### **FRAMING:**

30 mm x 30 mm (1.18" x 1.18") Square Aluminum extrusion with radius corners  
– 4 grooves 6.5 mm wide.

6060-T5 Alloy/Temper aluminum in clear satin anodized finish

Horizontal connecting mechanism with steel hammer-head bolt.

Assembly with 4 mm Allen Screw driver

Shipped disassembled in cartons on pallets – Assembly instructions supplied

### **PANELS - 41" W:**

#### Option 1

5 mm thick MDF core with vinyl laminate on both sides in off-white color

Fire rating Class III

For in-door use only

UL test results attached

#### Option 2

5 mm thick solid PVC available in white and basic colors

Fire rating Class A

In-door and out-door use

Manufacturers Fire Characteristics attached

### **ACCESSORIES:**

Aluminum U-Channel – mill finish

Aluminum L brackets and hinges

Plastic End caps

### **LOAD BEARING:**

The Mallforms wall system is a temporary structure and not intended as a load-bearing wall. Load bearing depends on the individual set-up. The walls can be secured to the ceiling, floor and existing walls with the L-brackets. On straight run walls where there are no ceiling attachments a 14" wide wing wall is used for support every 12 linear feet.